

REMOVE GRANITE TIPDOWNS AND
INSTALL APPROXIMATELY 33 LF OF NEW
GRANITE CURB AND SIDEWALK PER
DETAILS IN FIGURE 4

WINDHAM CENTER ROAD

REMOVE GRANITE TIPDOWNS AND
INSTALL APPROXIMATELY 39 LF OF NEW
GRANITE CURB AND SIDEWALK PER
DETAILS IN FIGURE 4

CMP 80

STOP

CMP 79

CMP 78

MULTIPLE 5" M...
W

REMOVE AND PROPERLY
DISPOSE OF ALL EXISTING
PAVEMENT AND ADD 4"
OF LOAM, SEED AND
MULCH TO ALL OPEN AND
DISTURBED AREAS

DOUBLE 24" ASH

17 SPACES

14 SPACES

14 SPACES

153' X 120' GRAVEL PARKING AREA

15 SPACES

APPROXIMATE
WELL LOCATION

WATER
QUALITY
FILTER

SIGN (BY
OTHERS)
MATCH
EXISTING
PAVEMENT

GRAVEL ACCESS
18' WIDE

R25'

R50'


SAWCUT AND REMOVE
PAVEMENT AND CURB AS
NECESSARY IN THIS AREA

POTENTIAL STRIPING
(BY OTHERS)


GARDEN

24" ASH

30" WHITE PINE



GRAPHIC SCALE



1 inch = 40 ft.

DH
DeLuca-Hoffman Associates, Inc.
778 MAIN STREET, SUITE 8
SOUTH PORTLAND, ME 04106
(207) 775-1121
DHAI@DELUCAHOFFMAN.COM

DRAWN:	DMB	DATE:	JULY 2011
DESIGNED:	OSC	SCALE:	1"=40'
CHECKED:	DDA	JOB NO.:	2146.19
FILE NAME:	2146.19-SP		

RSU #14
WINDHAM SCHOOL CAMPUS

GRAVEL PARKING NORTHEAST OF FIELD #10
SITE LAYOUT AND REMOVALS PLAN

FIGURE

1